# 1/2 HP AC CHAIN DRIVE WI-FI GARAGE DOOR OPENER

A complete, reliable solution with powerful performance.



# **RELIABLE**

1/2 HP AC MOTOR IS PURPOSEFULLY DESIGNED AND BUILT TO LAST.

CHAIN DRIVE SYSTEM FOR STEADY PERFORMANCE AND INDUSTRIAL STRENGTH.

WARRANTY LIFETIME MOTOR, 1-YEAR PARTS.

# SECURE

SECURITY+ 2.0° SAFEGUARDS GARAGE ACCESS BY SENDING A NEW CODE WITH EVERY CLICK.

POSILOCK® ELECTRONICALLY PROTECTS AGAINST FORCED OPENINGS.

ALERT-2-CLOSE SIGNALS WHEN A DOOR IS BEING CLOSED BY mvQ®.

THE PROTECTOR SYSTEM® INVISIBLE LIGHT BEAM AUTO-REVERSES THE DOOR IF THERE IS AN OBSTRUCTION.

# SMART

BUILT-IN WI-FI FOR THE EASIEST WAY TO CONNECT THE GARAGE.

myQ TECHNOLOGY ALLOWS USERS TO KNOW THEIR HOME IS SECURE.

REAL-TIME ALERTS INDICATE THE STATUS OF THE GARAGE DOOR VIA EMAIL OR PUSH NOTIFICATIONS.

MONITOR AND CONTROL THE OPENER FROM ANYWHERE USING MOBILE DEVICES.

Smartphone not included.

## **INCLUDED ACCESSORIES:**

### **MULTI-FUNCTION CONTROL PANEL®**

Turns on garage door opener lights from inside the garage.



(2) 3-BUTTON REMOTE CONTROLS

Operate up to 3 openers.



### WIRELESS KEYLESS ENTRY

Provides convenient, secure access from outside the garage with a 4-digit PIN.



### **POWERFUL ADD-ONS:**

### **MVO HOME BRIDGE**

Adds Apple® HomeKit™ compatibility and Siri® voice control to Wi-Fi-enabled openers. Installs easily in the garage within Wi-Fi range.\*\*



Works with Apple HomeKit

### MINI UNIVERSAL REMOTE CONTROL

Compact and portable to provide quick, easy garage access.



# MASTERFUL ENGINEERING.

1/2 HP AC CHAIN DRIVE WI-FI®
GARAGE DOOR OPENER

### MOTOR

MECHANICS



- 1/2 Horsepower AC
- -1,625 RPM
- Automatic Thermal
- Permanent Lubrication

Adjustable Door Arm)

**Environmental Conditions** 

- Steel Chassis, T-Rail and Trolley

- Electronic Limits for Easy Setup

### POWER -



- Full Chain Drive Mechanism (16:1 Gear Reduction and

 AC Wi-Fi Logic Board with Built-In Surge Suppressor (for Replacement Logic Boards, Order Part 050ACTWF)


- Auto-Force Adjustment for Changing Weather and

- -60 Hz Voltage
- 2.7A Current Rating
- -III Listed

-120V AC

-4' Power Cord (3-Prong)

### DIMENSIONS



iftMaster

Headroom Clearance Required: 2"

2053

ЛΠ

Per second

to move

upward

SPEED

7 II Per second

for door to move downward

### SPEEL

# STANDARD SPECS.

# **ECURITY**

### RADIO CONTROLS

Operating Range: ~2001

Operating Temperature: -35°F to 150°F

SECURITY+ 2.0®

(2) 3-Button Remote Controls (893LM) and Wireless Keyless Entry (877LM)

- Remote Controls: Security+ 2.0 - Keyless entry: Security+ 2.0
- Garage Door Opener: Security+ 2.0
- -Anti-Burglary Coding

### myQ® RADIO



- Provides 2-way communication from garage door opener and myQ Accessories.
- Enables monitoring and control of garage door openers via smartphone or tablet.

# LIGHTING





- Max. 2 100-Watt Lightbulbs
- Solid-State Light Delav
- Adjustable Time
- Enhanced CFL (Compact Fluorescent) Compatible, Max. 26 Watts

### **ENCRYPTED CONTROLS**

Multi-Function Control Panel® (882LMW)

- Program Remote Controls
- Maintenance Alert System
- Easy Wi-Fi Setup

# HOMELINK® COMPATIBLE (VERSION 4.0 OR HIGHER\*)

\*May require an external adapter depending on the model and year of your vehicle. Visit HomeLink.com for additional information.

# SHIPPING.

# SHIPPING WEIGHT (in lbs.)







### CARTONS (2)

CARTON 1: 20" x 12" x 10"

- -Garage Door Opener Head (8365W)
- Multi-Function Control Panel (882LMW)
- -(2) 3-Button Remote Controls (893LM)
- Wireless Keyless Entry (877LM)
- -The Protector System® Safety Reversing Sensors

CARTON 2: 10'4" x 5" x 5" (for 7' Rail)

- Assembled Solid-Steel Chain T-Rail

### CONVENIENCE AND SAFETY.

- Alert-2-Close/Unattended Close Operation (with Select Accessories)<sup>†</sup>
- Emergency/Quick Release
- Automatic Trolley Reconnect
- Ventilation/Pet Opening
- Down Safety Reverse
- Up Safety Stop

- Maintenance Alert System
- Garage Door Opener
  Capacity of up to 24 Remote
  Controls, 2 Wireless Keyless
  Entry Systems and 16 myQ
  Devices

\*WARNING: to reduce the risk of injury to persons—ONLY enable Timer-to-Close and myQ remote operation features when opener is installed on a sectional door.